

Colors



(E) - in

HIWAY 000346-0091

Men's two-tone, high-visibility lightweight jacket with 3M stripes, detachable sleeves, plastic zip with metal pull, elasticated cuffs, two front pockets, one breast pocket with zip and mobile phone pocket, padded, fleece inside collar, one inner pocket. **Composition:** 100% POLYESTER Appearance: OXFORD 300D Weight: 190 GR/MQ Sizes: Packaging: 1/5

MADE IN: MADE IN CHINA HS CODE: 62102000

69/73



67/71

| Size Guide | | | | | | | | | | | | | | | | W | Washing instructions | | | | | | | |
|--------------------------|-------------|------|-------|-------|---------|---------|---------|------|------------|-------|----------------------|------------|---------------|--------|------------|------------------|----------------------|-------|---------------|-------------------|-----------|-----------|--------------|---------|
| | | | | | | | | | | | | | | | | | ľ | 30 | \bigotimes | \boxtimes | | \bowtie | \bigotimes | MAX 25X |
| International Sizes | XXS | XS | XS S | | | ML | | | XL XXL 3XL | | | | 4X | | 5XL | | | | | | | | | |
| IT - DE | 36 38 | 40 4 | 2 44 | 46 | 48 | 50 52 | 54 | 56 | 58 | 60 | 62 6 | 64 66 | 68 | 70 7 | 2 74 | | | | | | | | | |
| FR - ES | 32 34 | 36 3 | 8 40 | 42 | 44 | 46 48 | 50 | 52 | 54 | 56 | 58 6 | 62 62 | 64 | 66 6 | 8 70 | | | | | | | | | |
| UK | 29 30 | 31 3 | 3 34 | 36 | 38 | 39 41 | 42 | 44 | 46 | 47 | 48 5 | 0 52 | 53 | 55 5 | 6 58 | | | | | | | | | |
| (G) - <i>cm</i> | 37 37 | 38 3 | 8 39 | 39 | 40 | 40 41 | 41 | 42,5 | 42,5 | 44 | 44 4 | 5 45 | 46 | 46 4 | 7 47 | | | ertif | ication | IS | | | | |
| (G) - in | 141/2 141/2 | 15 1 | 5 15½ | 15½ | 153/4 1 | 15¾ 16 | 16 | 16¾ | 163/4 1 | 17¼ 1 | 71/4 17 | 73⁄4 173⁄2 | 18 | 18 18 | 31/2 181/2 |) (-G) | \ [| | EN 14058:2017 | _ | | | | |
| (A) - cm | 72 76 | 80 8 | 4 88 | 92 | 96 1 | 100 104 | 108 | 112 | 116 | 120 1 | 24 12 | 28 132 | 136 | 140 14 | 44 148 | (\) m / | () r | | | 2 EN ISO 20471 | ~ ~ | | | |
| (A) - in | 28 30 | 31 3 | 3 34 | 36 | 38 | 39 41 | 42 | 44 | 46 | 47 | 48 5 | 0 52 | 53 | 55 5 | 6 58 | | | i | | | CE II CAT | | | |
| (B) - <i>cm</i> | 64 68 | 72 7 | 4 76 | 80 | 84 | 88 92 | 96 | 100 | 104 | 108 7 | 112 1 [.] | 16 120 | 124 | 128 13 | 32 136 | | - | | × | EN ISO 20471 | | | | |
| (B) - <i>in</i> | 25 27 | 28 2 | 9 30 | 32 | 33 | 34 36 | 38 | 40 | 41 | 43 | 45 4 | 6 48 | 49 | 51 5 | 52 54 | | | | | | | | | |
| (C) - <i>cm</i> | 80 84 | 88 9 | 0 92 | 96 | 100 1 | 104 108 | 3 112 | 116 | 120 | 124 🤇 | 128 13 | 32 136 | 140 | 144 14 | 48 152 |] !) () (| | | | | | | | |
| (C) - in | 31 33 | 34 3 | 5 36 | 38 | 39 | 41 42 | 44 | 46 | 47 | 49 | 50 5 | 52 53 | 55 | 56 5 | 8 59 | | | | | | | | | |
| (D) - cm | 82 82 | 84 8 | 4 85 | 85 | 86 | 86 87 | 87 | 88 | 88 | 88 | 88 8 | 8 88 | 89 | 89 8 | 9 89 | | | | | | | | | |
| (D) - in | 32 32 | 33 3 | 3 33 | 33 | 33 | 33 34 | 34 | 34 | 34 | 34 | 34 3 | 4 34 | 35 | 35 3 | 5 35 | | | | | | | | | |
| (E) - <i>cm</i> | 170/181 | | | | | 175/187 | 175/189 | | | | | | | |] | | | | | | | | | |
| | | | | 00/70 | | | | | 00/75 | | | | I ' / I I I I | | | | | | | | | | | |





69/75

 $\Lambda \Lambda$